

3/22/2017

LIMITED QUANTITIES AVAILABLE

Project:	
Catalog#:	
Approved by:	

Low Bay Aluminum 22"

(Acrylic Drop Lens)

MH / 250 watts

Applications

Ideal for lighting warehouses, industrial and retail facilities with low to medium ceiling heights

Features

- Die-cast housing with electrical box (lamp included)
- Acrylic drop lens



LOW BAYS

HID/CFL Fixtures



ORDERING INFORMATION

Catalog #	Watts	Volts †	Ballast	ANSI	Lamp Part #
ILAL22-250--MH-4T	250 MH	4T	CWA	M57/E	MH250/U

ACCESSORIES


Catalog #	Description
22ACR	22" acrylic reflector
SC	Insulated 3' steel safety cable with clear vinyl coating (includes a steel eye on one end and a loop on the opposite end)
SSH2	Malleable screw-shut hook
SPMRP	Swivel pendant mount round plate with a ball that allows the fixture to hang straight (mount to standard electrical box; fits 3/4" conduit)
CS480	480v cordset with NEMA L8-20 twist lock plug (custom lengths available)

DIMENSIONS



PHOTOMETRICS

400W MH @ 15' Mounting Height
Isofootcandles



† 4T = 120, 208, 240, 277 volts (pre-wired to 277)

Specifications subject to change without notice.

