

3/22/2017

LIMITED QUANTITIES AVAILABLE

Low Bay Aluminum 16"

(Enclosed - Acrylic Drop Lens)

MH / 250 watts

Applications

Ideal for lighting warehouses, industrial, and retail facilities with low to medium ceiling heights

Features

- Die-cast housing with electrical box (lamp included)
- Acrylic drop lens
- Adjustable accessory bracket

Project:	
Catalog#:	
Approved by:	



HID/CFL Fixtures



ORDERING INFORMATION

Catalog #	Watts	Volts †	Ballast	ANSI	Lamp Part #
LAL16-250-MH-4T	250 MH	4T	CWA	M57/E	MH250/U
LAL16-250-MH-5T	250 MH	5T	CWA	M57/E	MH250/U


ACCESSORIES (sold separately)

Catalog #	Description
QR	120v quartz restrike with socket, bracket, and dual contact bayonet (250 watt halogen lamp included)
HL	250 watt halogen lamp (fits 120v restrike socket and bracket)
SC	Insulated 3' steel safety cable with clear vinyl coating (includes a steel eye on one end and a loop on the opposite end)
SSH2	Malleable screw-shut hook
SPMRP	Swivel pendent mount round plate with a ball that allows the fixture to hang straight (mount to standard electrical box; fits 3/4" conduit)

DIMENSIONS



PHOTOMETRICS



† 4T = 120, 208, 240, 277 volts (pre-wired to 277)
5T = 120, 208, 240, 277, 480 volts (pre-wired to 277)

Specifications subject to change without notice.

