

5/1/2017

Large Flood

HPS / 150 - 400 watts | PS / 250 - 400 watts

Applications

Great for lighting building facades, displays, signs, or for general security lighting purposes

Features

- Die-cast housing with hinged door frame for easy relamping (lamp included)
- Textured bronze finish
- Tempered glass lens
- Includes factory installed 3-ft SEOW cord
- UL listed for wet locations
- EPA = 2.27 sq. ft.; Max. fixture weight = 37 lbs.

RAPID SHIP MODELS AVAILABLE FOR NEXT DAY SHIPMENT

- LFL-250-PS-4T-A
- LFL-400-PS-5T-A
- LFL-400-PS-5T-B

Project:	
Catalog#:	
Approved by:	



ORDERING INFORMATION						
Catalog #	Watts	Volts †	Ballast	ANSI	Lamp Part #	
LFL-150-HPS-4T	150 HPS	4T	HX-HPF	S55	LU150/55	*
LFL-250-HPS-5T	250 HPS	5T	CWA	S50	LU250	*
LFL-400-HPS-4T	400 HPS	4T	CWA	S51	LU400	*
LFL-400-HPS-480	400 HPS	480	CWA	S51	LU400	*
LFL-250-PS-4T	250 PSMH	4T	PS-CWA	M153/E	MH250/U/PS	(E)
LFL-320-PS-4T	320 PSMH	4T	PS-CWA	M154/E	MH320/BU/PS	*
LFL-350-PS-4T	350 PSMH	4T	PS-CWA	M131/E	MH350/BU/PS	*
LFL-400-PS-4T	400 PSMH	4T	PS-CWA	M155/E	MH400/U/PS	*
LFL-400-PS-5T	400 PSMH	5T	PS-CWA	M155/E	MH400/U/PS	(E)

ACCESSORIES (sold separately)		
Catalog #	Description	
LFLGS	Glare shield that can be reverse mounted to use as a back cutoff	*
LFLVG	Vandal resistant, clear polycarbonate PC guard	*
LFLB	Baffle with a black powder-coat finish	*
MFSB	Stamped, two-piece swivel bracket in a bronze finish	
MFLSF	Bronze-finished die-cast slip fitter with mounting hardware and angle indicators	

FACTORY INSTALLED OPTIONS		
Catalog #	Watts	Accessory Code *
MFSB	Stamped, two-piece swivel bracket in a bronze finish	A
MFLSF	Bronze-finished die-cast slip fitter with mounting hardware and angle indicators	B

* When ordering, include the Accessory Code with the catalog number (e.g., LFL-150-HPS-4T -A)

*LIMITED QUANTITIES AVAILABLE

† 4T = 120, 208, 240, 277 volts (pre-wired to 277)
 5T = 120, 208, 240, 277, 480 volts (pre-wired to 277)
 480 = 480 volts

Circle E logo indicates that this product complies with federal energy efficiency requirements.



Specifications subject to change without notice.

DIMENSIONS

MOUNTING DETAIL - MFSB

PHOTOMETRICS

400W PSMH @ 15' Mounting Height and aimed 30° Below Horizontal
 Isofootcandles