

3/15/2017

Limited Quantities Available

Large Wallpack

HPS / 250 watts | PS / 250 watts

Applications

Ideal for lighting parking facilities, entry ways, perimeters, pathways, and underpasses

Features

- Die-cast aluminum housing with hinged door frame (lamp included)
- Textured bronze finish with Borosilicate molded glass lens
- 1/2" conduit access, sides, top, or rear knockouts
- Photocell adaptable and UL listed for wet locations

Project:	
Catalog#:	
Approved by:	



ORDERING INFORMATION



Catalog #	Watts	Volts †	Ballast	ANSI	Lamp Part #
LWP-250-HPS-4T	250 HPS	4T	CWA	S50	LU250
LWP-250-HPS-5T	250 HPS	5T	CWA	S50	LU250
LWP-250-HPS-480	250 HPS	480	CWA	S50	LU250
LWP-250-PS-4T	250 PS	4T	PS-CWA	M153	MH250/BU/PS



ACCESSORIES (sold separately)


Catalog #	Description
LWPFC	Full cutoff with textured bronze finish
LWPSC	Side cutoff with textured bronze finish
LWPVG	Clear polycarbonate vandal guard
BPC120	Button photocell - 120v
BPC208/277	Button photocell - 208 or 277v

DIMENSIONS



PHOTOMETRICS

250W PSMH @ 15' Mounting Height
Isofootcandles



† 4T = 120, 208, 240, 277 volts (pre-wired to 277)
5T = 120, 208, 240, 277, 480 volts (pre-wired to 277)
480 = 480 volts

Circle E logo indicates that this product complies with federal energy efficiency requirements.



Specifications subject to change without notice.