

5/2/2017

## Mid-Size Wide Flood

PS / 150 watts | CF / 52 watts

### Applications

Perfect for lighting building facades, displays, signs, or for general security lighting purposes

### Features

- Die-cast housing with hinged door frame for easy relamping (lamp included)
- Textured bronze finish with tempered glass lens
- 1/2" adjustable knuckle
- UL listed for wet locations
- EPA = 0.75 sq. ft.; Max. fixture weight = 15 lbs.

### RAPID SHIP MODEL AVAILABLE FOR NEXT DAY SHIPMENT

- MSWF-150-PS-4T

Project:	
Catalog#:	
Approved by:	



ORDERING INFORMATION					
Catalog #	Watts	Volts †	Ballast	ANSI	Lamp Part #
MSWF-150-PS-4T	150 PSMH	4T	HX-HPF	M102	MH150/U/MED <b>E</b>
MSWF-52-CF-MV	52 CF	MV	Electronic	-	(2) - CF26DT *

ACCESSORIES (sold separately)	
Catalog #	Description
MSFWG	Wire guard with stainless steel construction *
MSFGS	Black powder-coat finished glare shield that can be reverse mounted to use as a back cutoff *
MSFVG	Clear polycarbonate vandal guard *
FLGSTK	HID ground stake with position adjustable stabilizer, die-cast fitting that accepts 1/2" knuckle, and built in wiring compartment *

\*LIMITED QUANTITIES AVAILABLE

† MV = 120-277 Universal Input  
4T = 120, 208, 240, 277 volts (pre-wired to 277)

Specifications subject to change without notice.

Circle E logo indicates that this product complies with federal energy efficiency requirements.



DIMENSIONS

MOUNTING DETAIL

PHOTOMETRICS

150W PSMH @ 15' Mounting Height  
& aimed 30° Below Horizontal

isofootcandles