

5/5/2017

# Small Flood

HPS / 70 watts | PS / 70 - 100 watts | CF / 42 watts

## Applications

Great for lighting building facades, displays, signs, or for general security lighting purposes

## Features

- Die-cast housing with hinged door frame for easy relamping (lamp included)
- Textured bronze finish with tempered glass lens
- 1/2" adjustable knuckle
- UL listed for wet locations
- EPA = 0.56 sq. ft.; Max. fixture weight = 11 lbs.

**RAPID SHIP MODEL  
AVAILABLE FOR NEXT DAY SHIPMENT**

- SFL-100-MH-4T

Project:	
Catalog#:	
Approved by:	



### ORDERING INFORMATION

Catalog #	Watts	Volts †	Ballast	ANSI	Lamp Part #	
SFL-70-HPS-120	70 HPS	120	R-NPF	S62	LU70/MED	*
SFL-70-MH-4T	70 PSMH	4T	HX-HPF	M98	MH70/U/MED	*
SFL-100-MH-4T	100 PSMH	4T	HX-HPF	M90	MH100/U/MED	ⓔ*
SFL-42-CF-MV	42 CF	MV	Electronic	-	CF42TE/830	*

### ACCESSORIES (sold separately)

Catalog #	Description	
SFLWG	Wire guard with stainless steel construction	*
SFLGS	Black powder-coat finished glare shield that can be reverse mounted to use as a back cutoff	*
SFLVG	Clear polycarbonate vandal guard	*
FLGSTK	HID ground stake with position adjustable stabilizer, die-cast fitting that accepts 1/2" knuckle, and built in wiring compartment	*

\*LIMITED QUANTITIES AVAILABLE



† MV = 120-277 Universal Input  
4T = 120, 208, 240, 277 volts (pre-wired to 277)  
120 = 120 volts

Circle E logo indicates that this product complies with federal energy efficiency requirements.




Specifications subject to change without notice.

### DIMENSIONS



### MOUNTING DETAIL



### PHOTOMETRICS

