

LED Small Canopy
LSCHD45DMV



Project:	
Catalog#:	
Approved by:	

Specifications

Model:	LSCHD45DMV
Lumens:	4474 Lm
Watts:	36 W
Lumens/Watt:	124 Lm/W
CCT:	5000 K
Dimmable:	0-10 V
Multi-volt operation:	120-277 V

Features

- Rugged and durable aluminum housing
- Dark bronze polyester powder coat finish
- Polycarbonate refractor lens
- Nichia LEDs
- L70 lifespan: 50,000+ hours
- LED's available in 5000K/CRI >70
- Minimum starting temperature: -40°F
- Suitable for use up to 40°C (104°F) ambient temperatures
- Ceiling mount – can be wired from underneath
- Easy one person install
- Surface mounts with cover plate and tek screws or 4" square or 4" octagon J-box or conduit feed
- Can be pendant mounted with 1/2" conduit entry from top
- Housing includes four threaded and plugged 1/2" conduit entry points (all sides)
- Warranty: 5 years
- Listings: UL and cUL Listed for wet locations
- RoHS compliant

Applications

- | | |
|---------------|------------------|
| Parking areas | Underpasses |
| Entrances | Loading docks |
| Walkways | Recreation areas |

Description

LSCHD series LED Small Canopy is designed for easy one person ceiling and pendant installation. It replaces up to 150 watt HID fixtures. The long LED life, easy mounting, and great color rendering makes this fixture attractive for new or retrofit projects.

Benefits

- Designed for optimal thermal performance and long LED life
- Replaces up to 150W HID
- High system efficacy 124 Lm/W
- Easy one person install design
- System Tested and Approved by Howard Industries in Mendenhall, Mississippi
- Compliant with safety and performance standards



Dimensions: 8.9 in. x 8.9 in. x 5 in.



Visit www.designlights.org for the Qualified Products List

