

LED UFO High Bay
LUHB Series

Project:	
Catalog#:	
Approved by:	

Features

- Magnesium alloy heatsink
- Ultra-durable Powder Coat Paint
- Standard Color Black
- Comes standard with a high bay hanging hook
- Color Temperature: 5000K standard (cool white), other colors available (special order, lead times apply)
- Color Rendering Index (CRI): > 80
- Long LED life; L₇₀ > 50,000 hours
- Rated for Ambient Temperatures between -40°C/-40°F to 50°C/122°F
- Input Voltage: MV: 100 – 277V; 50/60 Hz
- Input Voltage: HV: 200 – 480V; 50/60 Hz
- Power Factor (PF) > 0.95
- Total Harmonic Distribution (THD) < 20%
- Dimmable: 0-10Vdc
- Distribution: 120° beam angle standard, 60/70/90° possible with reflector accessory (sold separately)
- UL/cUL Listed
- IP65
- Warranty: 5 years

Applications

- Warehouse
- Auditorium
- Retail Space
- Manufacturing Facility



LUHB - MV Models



LUHB - DHV Model



Installation Instructions



Zip File

Ordering Information

Model Series	CCT	Nominal Input Power	Input Voltage	Dimensions			Comparable to HID
				Diameter (in)	Height (in)	Weight (lbs)	
LUHB LED UFO High Bay	50 5000K	A: 100W, 13,000 Lm	MV 100-277V, 50/60 Hz	9.65	7.25	5.0	320W
		B: 150W, 19,500 Lm		11.00	7.95	7.5	400W
		C: 200W, 26,000 Lm		11.81	8.15	8.7	750W
		D: 300W, 40,500 Lm	HV* 200-480V, 50/60 Hz	11.45	10.07	17.6	1000W

*Call factory for lead time and minimum order quantities. Not DLC listed.

Accessories (sold in package quantities, additional charges apply for partial carton orders)



LUHB-ALR-60 (20 pcs/ctn)
60° Aluminum Reflector




LUHB-ALR-90 (20 pcs/ctn)
90° Aluminum Reflector




LUHB-PCR-70 (10 pcs/ctn)
70° Polycarbonate Reflector


Photometrics




60° Reflector



70° Reflector



90° Reflector



120°, Standard/no Reflector